

CIRANOVA®

SINCE 1929



VOC free
One coat oil
Top protection
16 colours



UNICO





Clear 7170



Natural 7253



Natural White 7250



White 7251



Extra White 7252



Smoke 7597



Chocolat 7255



Cherry Red 7370



Castle 7374



Concrete 7375



Clouds 7262



Wenge 7372



English Brown 7371



Mud 7373



Old Grey 7257



Black Ink 7261



Environment-friendly: 0% VOC

Durable protection

Time-saving. Finish in only 1 coat

Quick drying

Gives a natural look

16 trendy colors

Easy to maintain

Easy to repair

One coat. Top protection.

UNICO is a 1-coat VOC-free oil from the newest generation using renewable natural oils. Thanks to its special technology only one coat is needed to finish and protect your wooden floor. The combination of the oil with the hardener results in a fast drying and excellent chemical resistant finish.

Application:

Mix the oil with the hardener (100/30) and let the product rest for about 10 minutes. Apply the oil with a buffing machine, brush or cloth. Remove the superfluous oil within 15 minutes with a cloth or polishing machine. Check afterwards if the surface feels handdry.

Drying times

Slightly walkable after 24 hours drying depending on the type of wood, the temperature, the humidity...

Applying quantity

+/- 50 - 60 m²/liter per coat

Available sizes:

1 liter UNICO + 300 ml hardener
400 ml UNICO + 120 ml hardener

Resistance

	Water	Red wine	Vinegar	Coffee	Detergent	Ammonia
After 1h	5	5	5	5	5	4
After 6h	5	5	5	5	4	3
After 24h	5	5	4	4	4	3

1 Visible mark with surface damage

2 Visible mark without surface damage

3 Slight shine/color change

4 Light shine/color change


5 No visible change

NEW

OIL
LACQUER
SYSTEM

UNICO-FORTICO SYSTEM

To have the best possible protection with a minimum amount of maintenance, you can apply our anti-scratch lacquer FORTICO 2C on top of UNICO. By applying FORTICO 2C NATURAL on top of the UNICO, the natural look and feel of an oiled floor will be retained. If you want some more shine you can apply FORTICO 2C mat or Satin. For more information concerning the application of the FORTICO on top of the UNICO, please contact our technical team.



HIGH QUALITY WOODCARE PRODUCTS

Ciranova is a high quality brand produced by Debal Coatings, with more than 80 years of expertise in the field of finishing and maintenance products for wood flooring. In the comprehensive Ciranova range of products you will find a full system for the preparation, finishing and maintenance of both interior and exterior wood.

These systems have been developed in the company's own laboratories using the latest available raw materials on the market, combined with up-to-date formulas Ciranova can guarantee all its clients the best quality for all specific application methods.

www.ciranova.eu

Produced by Debal Coatings nv | Industrieweg 29 | B-8800 Beveren Roeselare - Belgium
Tel +32 (0)51 30 11 40 | Fax +32 (0)51 31 26 48 | ciranova@ciranova.be

CIRANOVA®
SINCE 1929

NEW FORMULA
extra cleaning - extra protection



TECHNICAL DATA SHEET

Flooring soap



5L

0,75L

PRODUCT DESCRIPTION

Flooring soap made of natural oils for the regular maintenance of oiled floors. Flooring soap cleans and nourish the floor.

TECHNICAL DATA

APPEARANCE	liquid
PH-GRADE	8,1

USE

This soap is very concentrated and guarantees optimum protection against dirt.

USER TIPS

Mix 4 to 5 small caps into 10 liter luke warm water. Apply the cleaning solution on the wood by floor cloth in the direction of the wood. Rinse the dirty floor cloth in clean water. Never clean afterwards with water, you may lose your protective layer.



DRYING TIMES

At least 1 hour at room temperature.



APPLYING QUANTITY

+/- 400 m²/ liter

AFTER TREATMENT

Use approximately once a month depending on the amount of dirt. The more it is used, the better the protection against dirt. If the oiled wooden floor becomes dull and dirty, it is better to rinse with Ciranova® Intensive Cleaner. After cleaning with Intensive cleaner apply maintenance oil Ciranova.

PRODUCT INFORMATION

Also available: Flooring Soap White Ciranova®.
Shelf life: up to 2 years if kept in closed packaging.

SPECIAL QUALITIES

Ciranova® Flooring Soap contains only natural raw materials. Ciranova® Flooring Soap helps feed the wood. Protect from frost.

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv
Industrieweg 29 - 8800 Beveren-Roeselare
Belgium

tel. +32 (0) 51 30 11 40

fax +32 (0) 51 31 26 48

ciranova@ciranova.be

Never use to much water on a wooden floor. To much water will damage the floor.

Intensive cleaner



0,75L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv
Industrieweg 29 - 8800 Beveren-Roeselare
Belgium
tel. +32 (0) 51 30 11 40
fax +32 (0) 51 31 26 48
ciranova@ciranova.be

PRODUCT DESCRIPTION

Natural cleaner to thoroughly clean oiled wooden floors.

TECHNICAL DATA

APPEARANCE	clear liquid
SOLID CONTENTS	23,3
DENSITY	1
ODOUR	linseed oil
PH-GRADE	9,9

USE

Cleans thoroughly oiled floors. can also be used to remove spots and dirt which can not be removed with flooring soap Ciranova.

APPLICATION

Mix Intensive cleaner 1/20 into luke warm water. Apply the solution on the floor with a mop, microfiber cloth or soft scrubbing brush in the direction of the wood. You can also use a buffing machine with a green pad to clean the floor. When the floor is very dirty, you can use the intensive cleaner more concentrated. afterwards, the floor must be with clear water to remove the intensive cleaner.



DRYING TIMES

2 à 4 hours at room temperature. Be sure the floor is completely dry before you oil the floor again.



APPLYING QUANTITY

With 1 liter, you can clean +/- 200 m².

AFTER TREATMENT

After cleaning the floor with intensive cleaner, always apply Maintenance oil Ciranova.

PRODUCT INFORMATION

Shelf life: 12 months in original and unopened packaging
Store frost-free

Never use too much water on a wooden floor. Too much water will damage the floor.

Check our website for a detailed application video: www.ciranova.eu

Maintenance oil



5L 1L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare

Belgium

tel. +32 (0) 51 30 11 40

fax +32 (0) 51 31 26 48

ciranova@ciranova.be

PRODUCT DESCRIPTION

Universal maintenance system for oiled wooden floors. For the maintenance of floors treated with flooring oil and UV-oil. Different colours available.

TECHNICAL DATA

FYSISCHE TOESTAND	fluid
APPEARANCE	dark yellow
SOLID CONTENT	26%

USE

To maintain floors treated with Hardwaxoil and UV-oil.

PREPARATION

With Hardwaxoil treated wood: remove soap rests with pure water and let dry. If strongly dirty, clean first with Intensive Cleaner Ciranova®.

USER TIPS

Apply a thin layer of Maintenance Oil Ciranova® and let impregnate for a few minutes. Wipe off with a clean cloth. Polish the oil well dry to avoid sticking.



DRYING TIMES

Do not charge the first 12 hours!

The optimal hardness is reached after 48 hours. Don't use any water or maintenance products during this period.



APPLYING QUANTITY

50 m²/l for the maintenance of already treated wooden floors.

AFTER TREATMENT

It's recommended to treat the floor each year with Maintenance Oil Ciranova®.

SPECIAL QUALITIES

Used cloths need to be thrown into water after use, to increase flammability. The presence of linseed oil in the system causes this measure. Oil Refresh Ciranova® protects your parquet floor against water and your wood gets a natural view.